



FOR GOOD REASONS

pan**DOMO**[®] DMC

Dispersion sealer

Protective film ensuring, metal based acrylic dispersion, silk mat

For the first protection and maintenance cleaning
of oiled and sealed PANDOMO Floors

slip resistant

dirt repellent

long lasting

trafficable



Reg.No. 37344

Manufacturer
with certified quality system
as per DIN EN ISO 9001

ARDEX GmbH
58430 Witten · P.O. Box 61 20
GERMANY
Telephone: +49 (0) 23 02/664-0
Telefax: +49 (0) 23 02/664-437
kundendienst@ardex.de
www.ardex.de

Dispersion sealer

Areas of application:

Interior.

Pandomo DMC Dispersion Sealer is a protective coat for PANDOMO Floors sealed with PANDOMO SL Stone oil.

Properties:

- slip resistant
- repellent against short time exposure to liquids
- long lasting
- silk mat

PANDOMO DMC Dispersion sealer acts dirt repellent and gives the surface a silk mat appearance.

Application:

Shake well before use. Than apply the material fresh in fresh. Avoid wet edges.

Substrate preparation:

First application:

The first application has to be done undiluted in 2 coats with a lambsfur mob fresh in fresh. This application can be done 12 hours after the floor has been sealed with Pandomo SL Stone oil. Ensure that there is sufficient ventilation. Generally do not flood the floor always apply in a mist like consistency. Observe the installation instructions for PANDOMO SL.

Between the first and the second coat wait at least 60 minutes at +20 °C and 60 % RH depending on the ambient temperatures.

Important notice:

Do not use or mix PANDOMO DMC together with other cleaning and care products. Do not use for daily cleaning.

As long as the PANDOMO DMC applied floor is still shiny do not traffic or brush the floor. Clean tools immediately after application with water. On dark PANDOMO Floors you may encounter mat shades on the first coat. After the 2nd coat is applied these shades will vanish.

Full resistance is achieved after 5–7 days (depending on the climatical conditions).

Daily cleaning:

For the daily cleaning PANDOMO WP has to be used. First clean the area with a broom or with the Vacuum cleaner brush to remove dust, dirt and sand, because this materials could act like a sand paper.

Depending on the usage add 50 ml PANDOMO WP Care Liquid in 10l clean water and wipe the floor.

Basic cleaning:

For initial cleaning and entrained dirt please use PANDOMO BC. See technical data sheet for instructions.

Note:

In case of contact with the eyes, rinse immediately also under the eyelid with water. In case of contact with the skin, wash with water and soap. If swallowed rinse mouth with water and drink plenty of water.

Try not to vomit, If necessary consult a doctor.

No special precautions to fire and explosive hazard. No marking as per dangerous goods requirement. Avoid exposure to temperatures above +35 °C.

Technical data

According to ARDEX quality standards:

Specific weight: Approx 1.0 kg/l

PH-Value: 8.5

Consumption: Approx 25 g/m² for single coat, equivalent to 50 g/m² for mandatory double coat

Fire protective measurements: Not needed

Classificaiton as per regulations for hazardous materials: none

Packaging: Container with 3 l

Storage: can be stored for approx. 12 months in dry rooms in closed packaging

Product code for Cleaning companies: GG10